## CERTIFICATE OF COMPLIANCE

Certificate Number Report Reference Issue Date	20160127-E188110 E188110-20060518 2016-JANUARY-27
Issued to:	SHANGHAI LONG-JOIN ELECTRONICS CO LTD NO 398 NAN WENZAO RD, BAOSHAN, SHANGHAI, 200443 CHINA
This is to certify that representative samples of	COMPONENT - PHOTOCONTROLS, PLUG-IN, LOCKING TYPE See Addenum Page
	Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.
Standard(s) for Safety:	UL 773 PLUG-IN, LOCKING TYPE PHOTOCONTROLS FOR USE WITH AREA LIGHTING CSA C22.2 NO. 182.2-M1987 INDUSTRIAL LOCKING TYPE, SPECIAL USE ATTACHMENT PLUGS, RECEPTACLES AND CONNECTORS
Additional Information:	See the UL Online Certifications Directory at <u>www.ul.com/database</u> for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. The final acceptance of the component is dependent upon its installation and use in complete equipment submitted to UL LLC.

Look for the UL Certification Mark on the product.

a malle ant Chief Engineer, Global Inspection and Field Services Bruce Ma

Ս

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, plea contact a local UL Customer Service Representative at <u>http://ul.com/aboutul/locations/</u>

UL LLC

## CERTIFICATE OF COMPLIANCE

**Certificate Number Report Reference Issue Date** 

20160127-E188110 E188110-20060518 2016-JANUARY-27

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Plug-In, Locking Type Receptacle, Models JL-200X, followed by 16, 14 or 12, may be followed by two numerical characters. Model JL-230, followed by 16 or 14, may be followed by two numerical characters. Models JL-240 or JL-240T, followed by X or Y, followed by A or B, followed by 14 or 16, may be followed by G, followed by two numerical characters, may be followed by R. Models JL-220, followed by 14 or 16, 18 followed by two numerical characters, followed by alphanumeric characters. Models JL-240TL, JL-250C and JL-250H followed by XXXXXX

Locking Type Plug, Models JL-241J and JL-241JF

**San Walks** Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services UL LLC

